

Reference Guide

Developed for Vermont Department of Health



SensoScientific, Inc. 685 Cochran Street, Ste. #200, Simi Valley, CA 93065 www.sensoscientific.com

TABLE OF CONTENTS

Cloud Portal Login	
Change Password	
Monitor Nodes	5
Audit Nodes	6
Confirm Alarms	7
Turn Off Audible Alarm	8
Audit Node Report	
Battery Status	
Contact Us	



CLOUD PORTAL LOGIN

Use the SensoScentific Cloud Portal to view data logger records.

Initial Login





CHANGE PASSWORD

Create new passwords.

- **1** Select the **"CONFIGURATION" tab** in the main menu.
- 2 Select the "User" tab in the submenu.
- 3 The submenu will reveal new options. Select the "Change Password" tab.
- 4 Fill out the fields and click the **"Change Password" button**.

Genso scier	tific.
	ALARM MONITORING REPORT CONFIGURATION CALIBRATION HELP
Company	Chaptro Password
Nodes	Change rassword
User	<2
New User	You are about to change password for user : <i>demo</i>
Configure	Old Password :
Add/Remove Node	New Password :
Change Password	
Group	Confirm New Password :
Settings	Change Password
Notification	



MONITOR NODES

View assigned nodes and check their current status.

- **1** Select the **"MONITORING"** tab in the main menu.
- **2** You will be automatically redirected to the **"Current Status" page**.
- **3** Each node will change color based on its **current status**.





AUDIT NODES

Confirm that you have viewed a node's current status.

- **1** Select the **"MONITORING"** tab in the main menu.
- **2** Mark the checkbox in the rightmost column of the node(s) you want to audit.
- **3** Click the **"Audit Node" button** at the bottom of the page.

Genso scier,	ntific	9		(
		Α	LARM		NITORIN	IG RE	PORT	CO	NFIGURATIO	N CA	LIBRATION	HELI)
Current Status							Cur	ront	Statuc				
Battery Status							COL		วเลเนร				
Posot Min/Max													2
Reset Willing Widx													V
	Node Name	Node ID	Location	Alarm High	Alarm Low	Alarm Delay	Value	Graph	Last Updated	Value Status	Connectivity Status	Alarm Status	Notification Status
	Lab Light	28329	Laboratory	N/A	N/A	60 (Mins)	No Light	24 Hrs	4/9/2019 2:23:42 PM	Out of Range	Connected	Alarmed	Active
	99984E3DD	1249	Dietary	90 (°C)	-40 (°C)	30 (Mins)	83.7 (°C)	24 Hrs	4/9/2019 2:42:36 PM	In Range	Connected	Alarmed	Active 🗸
	C8FD197B_T	1245	Room 5	90 (%RH)	-40 (%RH)	15 (Mins)	30 (%RH)	24 Hrs	4/9/2019 2:33:25 PM	In Range	Disconnected	Alarmed	Active 🗸
	OR	11545	Pharmacy	8 (°C)	2 (°C)	0 (Mins)	7.6 (°C)	24 Hrs	4/9/2019 3:15:52 PM	In Range	Disconnected	Alarmed	Suspended 🗹
	Temp 1	1247	Dietary	70 (%RH)	20 (%RH)	1 (Mins)	72 (%RH)	24 Hrs	4/9/2019 3:21:33 PM	Out of Range	Connected	Alarmed	Suspended 🗸
	Temp 2	86025	Dietary	90 (°F)	-40 (°F)	30 (Mins)	21.1 (°F)	24 Hrs	4/9/2019 2:44:52 PM	In Range	Connected	No Alarms	Active
	Walk In	46422	FoodService	46 (°F)	36 (°F)	30 (Mins)	30 (°F)	24 Hrs	4/9/2019 2:17:55 PM	In Range	Connected	No Alarms	Active 🗹
	9884E3DD	86029	OR	85 (%RH)	30 (%RH)	60 (Mins)	60 (%RH)	24 Hrs	4/9/2019 2:21:28 PM	In Range	Connected	No Alarms	Active 🗹
	Cafe	86030	NapaCafe	8 (°C)	2 (°C)	0 (Mins)	6 (°C)	24 Hrs	4/9/2019 3:44:42 PM	In Range	Connected	No Alarms	Active 🗹
	Lab Ambient	89949	Laboratory	90 (°F)	-40 (°F)	30 (Mins)	21.1 (°F)	24 Hrs	4/9/2019 3:07:11 PM	In Range	Connected	No Alarms	Active 🗹
	Vaccine	1246	Laboratory	30 (°C)	10 (°C)	90 (Mins)	28 (°C)	24 Hrs	4/9/2019 2:12:44 PM	In Range	Disconnected	No Alarms	Active
	Visitor	1248		45 (°F)	35 (°F)	15 (Mins)	42.5 (°F)	24 Hrs	4/9/2019 2:15:46 PM	In Range	Disconnected	No Alarms	Active
	PH Humid	11543	NapaCafe	8 (°C)	2 (°C)	30 (Mins)	5.2 (°C)	24 Hrs	4/9/2019 3:17:57 PM	In Range	Connected	No Alarms	Active
	Lab 2	11544	Laboratory	90 (°F)	-40 (°F)	30 (Mins)	21.1 (°F)	24 Hrs	4/9/2019 2:42:36 PM	In Range	Connected	No Alarms	Active
	Visitor 2	28327	Corporate	90 (°E)	-40 (°E)	15 (Minc)	21.1 (°F)	24 HIS	4/5/2019 5.44.42 PW	In Range	Connected	No Alarmo	Active
	9984E3D T	28328	NapaCafe	13.3 (°C)	12 (°C)	0 (Mins)	22.1 (°C)	24 Hrs	4/9/2019 2:22:56 PM	Out of Range	Disconnected	No Alarms	Active
	A	udit	Node										



CONFIRM ALARMS

Document the cause of alarms.

- **1** Select the **"MONITORING"** tab in the main menu.
- 2 Click the "Alarmed" button of the desired node. (Not Displayed)
- 3 Click the "Take Action" button to confirm the alarm. (Not Displayed)
- 4 Fill out the fields and click the **"Confirm" button**.

Genso scieri	ntific. alarm i		REPORT CON	NFIGURAT	ION CALIBRATION	N HELP
Diagnose Alarm			Diagnose	Alarm		
	Node Name	Node ID	Node Ty	pe	Alarm Date	Alarm Type
	Lab Light 28329 Light Sensor 4					Data Alarm
	Root Cause: Other Detail Description (optiona Corrective Action (Max 500 Is the equipment v Confirm	vorking proper	·ly? ● Yes	⊖No ◄	If the vacuunit is not properly, y option to s node . This alarm not the design duration.	ine storage working you have the suspend the swill stop fications for hated



TURN OFF AUDIBLE ALARM

Deactivate a node's audible alarm.

- 1 Select the "MONITORING" tab in the main menu.
- **2** Click the **speaker icon** of the node you want to silence.





AUDIT NODE REPORT

Generate a report of all audited nodes.

- **1** Select the **"REPORT" tab** in the main menu.
- 2 Select the **"Audit Node" tab** in the submenu.
- **3** Specify the parameters and click the **"Show Report" button**.





BATTERY STATUS

Check the battery status of your assigned nodes.

- **1** Select the **"MONITORING"** tab in the main menu.
- 2 Select the **"Battery Status" tab** in the submenu.
- **Each node will change color based on its current battery status**.





CONTACT US

Vermont Department of Health Immunization Program

108 Cherry Street Burlington, VT 05401

P. (802) 863-7638 or 1-800-640-4374 ahs.vdhimmunizationprogram@vermont.gov

